acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

1 Identification

· Product identifier

· Trade name: Tire Mounting Paste

· Article number: 14-700, 14-701, 14-705, 14-706

· Recommended use and restriction on use

· Recommended use:

Lubricant

Tire maintenance.

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

31 Incorporated 100 Enterprise Dr.

Newcomerstown, OH 43832 Phone: (740) 498-8324

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Repr. 1 H360 May damage fertility or the unborn child. Route of exposure: Oral.

STOT RE 2 H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



CHSUS

- · Signal word: Danger
- · Hazard statements:

H360 May damage fertility or the unborn child. Route of exposure: Oral.

H373 May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

· Precautionary statements:

P260 Do not breathe mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection. P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

(Cont'd. on page 2)

Page: 2/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

P405

(Cont'd. of page 1)

Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:					
107-21-1	ethylene glycol	STOT RE 2, H373 Acute Tox. 4, H302	2.5-10%		
25322-68-3	polyethylene glycol		<2.5%		
102-71-6	2,2',2"-nitrilotriethanol		<2.5%		
1303-96-4	disodium tetraborate, decahydrate	Repr. 1B, H360 Eye Irrit. 2A, H319	<1%		

[•] Additional information: For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

Seek medical treatment in case of complaints.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Nausea in case of ingestion.

Gastric or intestinal disorders

Danger:

May damage fertility or the unborn child. Route of exposure: Oral.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture No relevant information available.

(Cont'd. on page 3)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 2)

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: No relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions No special measures required.
- Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

- Further information about storage conditions: Protect from frost.
- · Specific end use(s) No relevant information available.

(Cont'd. on page 4)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 3)

8 Exposure controls/personal protection

· Control paran	neters
· Components w	rith limit values that require monitoring at the workplace:
107-21-1 ethyle	ene glycol
TLV (USA)	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only
EL (Canada)	Short-term value: 20** mg/m³ Long-term value: 10** mg/m³ Ceiling limit value: 100* mg/m³, 50*** ppm *Aerosol; **Particulate; ***Vapour
EV (Canada)	Ceiling limit value: 100 mg/m³
LMPE (Mexico)	Ceiling limit value: 100* mg/m³ A4, *solo aerosol
25322-68-3 poly	yethylene glycol
WEEL (USA)	Long-term value: 10 mg/m³ (H); MW>200
102-71-6 2,2',2'	'-nitrilotriethanol
TLV (USA)	Long-term value: 5 mg/m³
EL (Canada)	Long-term value: 5 mg/m³
EV (Canada)	Long-term value: 3.1 mg/m³, 0.5 ppm
LMPE (Mexico)	Long-term value: 5 mg/m³
	dium tetraborate, decahydrate
REL (USA)	Long-term value: 5 mg/m³
TLV (USA)	Short-term value: 6* mg/m³ Long-term value: 2* mg/m³ *as inhalable fraction
EL (Canada)	Short-term value: 6 mg/m³ Long-term value: 2 mg/m³
EV (Canada)	Short-term value: 6 mg/m³ Long-term value: 2 mg/m³ inorganic, inhalable
LMPE (Mexico)	Short-term value: 6* mg/m³ Long-term value: 2* mg/m³ A4, *fracción inhalable

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

· Engineering controls: Provide adequate ventilation.

(Cont'd. on page 5)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 4)

· Breathing equipment:

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For spills, respiratory protection may be advisable.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection:

Not required under normal conditions of use.

Protection may be required for spills.

- · Limitation and supervision of exposure into the environment No special requirements.
- · Risk management measures No special requirements.

Information on basic physical ar	nd chemical properties	
Appearance:	id chemical properties	
Form:	Pasty	
Color:	Not determined.	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	410 °C (770 °F)	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)	

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 5)

Density: Not determined.
 Relative density: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Dispersible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid

Excessive heat and contact with acids.

Store away from oxidizing agents.

Incompatible materials

Oxidizing agents
Strong acids

· Hazardous decomposition products Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: No sensitizing effects known.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

(Cont'd. on page 7)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 6)

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): From product as supplied: None.
- · Repeated dose toxicity: Possible risk of irreversible effects.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: May damage fertility or the unborn child. Route of exposure: Oral.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure:

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

· Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packagings**
- · **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 8)

Page: 8/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 7)

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.	
· Transport hazard class(es)		
· DOT, ADR, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

107-21-1 ethylene glycol

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 22, 2017 Revision: June 22, 2017

Trade name: Tire Mounting Paste

(Cont'd. of page 8)

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency):

1303-96-4 disodium tetraborate, decahydrate

I (oral)

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision June 22, 2017 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxique

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Repr. 1: Reproductive toxicity – Category 1

Repr. 1B: Reproductive toxicity - Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com