

# Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

## 1 Identification

- **Product identifier**
- **Trade name: Heavy Duty Black Retread Cement**
- **Product code:** 14-516
- **Recommended use and restriction on use**
- **Recommended use:** Tire maintenance.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
31 Incorporated  
100 Enterprise Dr.  
Newcomerstown, OH 43832  
Phone: (740) 498-8324
- **Emergency telephone number:**  
ChemTel  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flam. Liq. 2 H225 Highly flammable liquid and vapor.  
Skin Irrit. 2 H315 Causes skin irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H336 May cause drowsiness or dizziness.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS02 GHS07
- **Signal word:** Danger
- **Hazard statements:**  
H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Cont'd. on page 2)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 1)

P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

142-82-5	Heptane	>80%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
8050-09-7	Rosin	1-5%
	<ul style="list-style-type: none"> <li>⚠ Skin Sens. 1, H317</li> </ul>	
1333-86-4	Carbon black	<1%

· **Additional information:**

For the wording of the listed Hazard Statements, refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

## 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

(Cont'd. on page 3)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 2)

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache  
Breathing difficulty  
Coughing, dizziness, if inhaled.  
Irritant to skin and mucous membranes.  
Allergic reactions  
Gastric or intestinal disorders when ingested.  
Disorientation

· **Indication of any immediate medical attention and special treatment needed:**

Contains Rosin. May produce an allergic reaction.  
Treat skin and mucous membrane with antihistamine and corticoid preparations.  
If necessary oxygen respiration treatment.  
Later observation for pneumonia and pulmonary edema.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Foam  
Carbon dioxide  
Fire-extinguishing powder  
Gaseous extinguishing agents  
Water fog / haze

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Highly flammable liquid and vapor.  
Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.  
Wear fully protective suit.

· **Additional information:** Eliminate all ignition sources if safe to do so.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation.  
Keep away from ignition sources.  
Protect from heat.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Absorb liquid components with non-combustible liquid-binding material.  
Allow to solidify. Pick up mechanically.

(Cont'd. on page 4)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 3)

· **Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Use only outdoors or in a well-ventilated area.  
Avoid contact with the eyes and skin.  
Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Highly flammable liquid and vapor.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.  
Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.  
Store away from oxidizing agents.

· **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**142-82-5 Heptane**

PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 85 ppm Ceiling limit value: 1800* mg/m <sup>3</sup> , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1635 mg/m <sup>3</sup> , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

**8050-09-7 Rosin**

TLV (USA)	Long-term value: NIC-0.01* mg/m <sup>3</sup>
-----------	--

(Cont'd. on page 5)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 4)

EL (Canada)	*inhalable fraction, NIC-DSEN, RSEN S(D), S(R)
LMPE (Mexico)	SEN, (L)
<b>1333-86-4 Carbon black</b>	
PEL (USA)	Long-term value: 3.5 mg/m <sup>3</sup>
REL (USA)	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m <sup>3</sup> IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m <sup>3</sup>
LMPE (Mexico)	Long-term value: 3* mg/m <sup>3</sup> A3, *fracción inhalable

## · Exposure controls

### · General protective and hygienic measures:

- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

### · Engineering controls:

- Take precautionary measures against static discharge.
- Store in a well-ventilated place.

### · Breathing equipment:

- Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.
- For spills, respiratory protection may be advisable.

### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### · Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

### · Body protection: Protective work clothing

### · Limitation and supervision of exposure into the environment

Avoid release to the environment.

### · Risk management measures No relevant information available.

(Cont'd. on page 6)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

Trade name: Heavy Duty Black Retread Cement

(Cont'd. of page 5)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · Appearance:

· Form:	Liquid
· Color:	Black
· Odor:	Solvent-like
· Odor threshold:	Not determined.

· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	>35 °C (>95 °F)

· Flash point:	-4 °C (24.8 °F)
----------------	-----------------

· Flammability (solid, gaseous):	Not applicable.
----------------------------------	-----------------

· Auto-ignition temperature:	~200 °C (~392 °F)
------------------------------	-------------------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
------------------------	--

#### · Explosion limits

· Lower:	~1 Vol %
· Upper:	~8 Vol %

· Oxidizing properties:	Non-oxidizing.
-------------------------	----------------

· Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
------------------------------------	-------------------

#### · Density:

· Relative density:	0.7-0.8
· Vapor density:	Not determined.
· Evaporation rate:	Not determined.

#### · Solubility in / Miscibility with

· Water:	Not miscible or difficult to mix.
----------	-----------------------------------

· Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

#### · Viscosity

· Dynamic:	Not determined.
· Kinematic at 40 °C (104 °F):	>20.5 mm <sup>2</sup> /s (Zahn Cup #4)

#### · Other information

No relevant information available.

## 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Highly flammable liquid and vapor.

(Cont'd. on page 7)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 6)

Reacts violently with oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Toxic fumes may be released if heated above the decomposition point.

· **Conditions to avoid**

Keep away from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

· **Incompatible materials** Oxidizing agents.

· **Hazardous decomposition products**

Under fire conditions only:

Carbon monoxide and carbon dioxide

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**142-82-5 Heptane**

Oral	LD50	>5000 mg/kg (rat) (Estimate)
------	------	------------------------------

· **Primary irritant effect:**

· **On the skin:** Irritant to skin and mucous membranes.

· **On the eye:** Based on available data, the classification criteria are not met.

· **Sensitization:** Sensitization possible through skin contact.

· **IARC (International Agency for Research on Cancer):**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

1333-86-4	Carbon black	2B
-----------	--------------	----

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

## 12 Ecological information

· **Toxicity**

(Cont'd. on page 8)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**



(Cont'd. of page 7)

- **Aquatic toxicity** Very toxic to aquatic life with long lasting effects.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.  
Do not allow product to reach ground water, water course or sewage system.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |          |
|---|----------|
| · <b>UN-Number</b>  |          |
| · DOT, ADR/RID/ADN, IMDG, IATA  | UN1206   |
| · <b>UN proper shipping name</b>  |          |
| · DOT, ADR/RID/ADN, IMDG, IATA  | HEPTANES |
| · <b>Transport hazard class(es)</b>   |          |
| · DOT   |          |
|  |          |
| · <b>Class</b>  | 3        |
| · <b>Label</b>  | 3        |
| · <b>ADR/RID/ADN</b>  |          |
|  |          |
| · <b>Class</b>  | 3 (F1)   |
| · <b>Label</b>  | 3        |

(Cont'd. on page 9)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

Trade name: Heavy Duty Black Retread Cement

(Cont'd. of page 8)

· **IMDG, IATA**



· **Class** 3  
 · **Label** 3

· **Packing group**

· **DOT, ADR/RID/ADN, IMDG, IATA** II

· **Environmental hazards**

· **Marine pollutant:**



Yes

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

(Cont'd. on page 10)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 9)

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4	Carbon black
-----------	--------------

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

142-82-5	Heptane	D
----------	---------	---

· **IARC (International Agency for Research on Cancer):**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

1333-86-4	Carbon black	2B
-----------	--------------	----

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

(Cont'd. on page 11)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: May 15, 2020

**Trade name: Heavy Duty Black Retread Cement**

(Cont'd. of page 10)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

### · Sources

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtel.com](http://www.chemtel.com)