Printing Date: June 28, 2024

Revision Date: June 28, 2024

1 Identification

· Product identifier

· Trade name: Bead Sealer

· Article number: 14-101, 14-101A, 14-101B, 41-431, 41-432

· Recommended use and restriction on use

- · Recommended use: Tire maintenance.
- · Restrictions on use: No relevant information available.

· Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier: 31 Incorporated 100 Enterprise Dr. Newcomerstown, OH 43832 Phone: (740) 498-8324

· Emergency telephone number:

ChemTel Inc.

(800) 255-3924 (North America)

(801) 1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

[·] Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms:



Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid and vapor.

H315+H320 Causes skin and eye irritation.

- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.

(Cont'd. on page 2)

Printing date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

	(Cont'd. of page 1)
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapors.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical	characterization: Mixtures		
· Compone	nts:		
142-82-5	heptane	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Eye Irrit. 2B, H320 	60-80
9006-04-6	natural rubber latex	Skin Sens. 1B, H317	10-20

4 First-aid measures

[•] Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

(Cont'd. on page 3)

Printing date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

	(Cont'd. of pag
Immediately wash with water and soap and rinse thoroughly.	
If skin irritation or rash occurs: Get medical advice/attention.	
After eye contact:	
Remove contact lenses if worn, if possible.	
Rinse opened eye for several minutes under running water.	
Seek medical treatment in case of complaints.	
After swallowing:	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; immediately call for medical help.	
A person vomiting while lying on their back should be turned onto their side.	
Most important symptoms and effects, both acute and delayed:	
Headache	
Dizziness	
Breathing difficulty	
Gastric or intestinal disorders when ingested.	
Irritant to skin and mucous membranes.	
Allergic reactions	
Disorientation	
Danger:	
Danger of impaired breathing.	
Vapours may cause drowsiness and dizziness.	
May be fatal if swallowed and enters airways.	
Indication of any immediate medical attention and special treatment needed:	
If swallowed, gastric irrigation with added, activated carbon.	
If necessary oxygen respiration treatment.	
If swallowed or in case of vomiting, danger of entering the lungs.	
Later observation for pneumonia and pulmonary edema.	
If medical advice is needed, have product container or label at hand.	

5 Fire-fighting measures

• Extinguishing media	
· Suitable extinguishing agents:	
Foam	
Carbon dioxide	
Gaseous extinguishing agents	
Water fog / haze	
· For safety reasons unsuitable extinguishing agents:	
Water stream.	
Water spray	
Special hazards arising from the substance or mixture	
Highly flammable liquid and vapor.	
Formation of toxic gases is possible during heating or in case of fire.	
Advice for firefighters	
Protective equipment:	
Wear self-contained respiratory protective device.	
Wear fully protective suit.	
······································	(Cont'd. on page 4)

Safety Data Sheet

Acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 3)

[•] Additional information:

Eliminate all ignition sources if safe to do so. Cool endangered containers with water fog.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation. Keep away from ignition sources.

Protect from heat.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Place in properly marked container for disposal.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

[·] Handling

Precautions for safe handling:

Use only outdoors or in a well-ventilated area.

Avoid splashes or spray in enclosed areas.

Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

• Conditions for safe storage, including any incompatibilities

· Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

- Store away from foodstuffs.
- Store away from oxidizing agents.

Specific end use(s) No relevant information available.

(Cont'd. on page 5)

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 4)

142-82-5 heptanPEL (USA)IREL (USA)ITLV (USA)IEL (Canada)I	th limit values that require monitoring at the workplace: e Long-term value: 2000 mg/m ³ , 500 ppm Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
PEL (USA) REL (USA) TLV (USA) EL (Canada)	Long-term value: 2000 mg/m³, 500 ppm Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min Short-term value: 2050 mg/m³, 500 ppm
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min Short-term value: 2050 mg/m³, 500 ppm
TLV (USA)	Ceiling limit value: 1800* mg/m³, 440* ppm *15-min Short-term value: 2050 mg/m³, 500 ppm
EL (Canada)	
	g (
	Short-term value: 500 ppm Long-term value: 400 ppm
	Short-term value: 2045 mg/m³, 500 ppm Long-term value: 1635 mg/m³, 400 ppm
Ì Í	Short-term value: 500 ppm Long-term value: 400 ppm
9006-04-6 natura	al rubber latex
	Long-term value: 0.0001* mg/m³ Skin; DSEN, RSEN;* inh. fraction
	Long-term value: 0.001 mg/m³ inhalable, Skin; S
	Long-term value: 0.001 mg/m³ as total proteins, inhalable, Skin
	Long-term value: 0.0001* mg/m³ SEN, PIEL, *fracción inhalable
The usual precau Keep away from Immediately remo Wash hands befo Do not inhale gas Avoid contact wit Engineering cor Take precautiona Do not expose to Store in a well-ve Breathing equip	tive equipment: ive and hygienic measures: utionary measures for handling chemicals should be followed. foodstuffs, beverages and feed. ove all soiled and contaminated clothing. ore breaks and at the end of work. ses / fumes / aerosols. h the eyes and skin. htrols: ary measures against static discharge. temperatures exceeding 50 °C/122°F. entilated place.

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

Limitation and supervision of exposure into the environment No relevant information available.

· Risk management measures No relevant information available.

Physical and chemical prope	rties
Information on basic physical a	nd chemical properties
Appearance:	
Form:	Liquid
Color:	Black
· Odor:	Solvent-like
Odor threshold:	Not determined.
· pH-value:	Not determined.
• Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.
· Flash point:	-4 °C (25 °F) (Heptane)
· Flammability (solid, gaseous):	Not applicable.
Auto-ignition temperature:	200 °C (392 °F) (Estimate)
Decomposition temperature:	Not determined.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air, vapor mixtures are possible.
· Explosion limits	
Lower:	1 Vol % (Estimate)
Upper:	8 Vol % (Estimate)
 Oxidizing properties: 	Not determined.
· Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
Density at 20 °C (68 °F):	0.75 - 0.79 g/cm³ (6.259 - 6.593 lbs/gal) (Estimate)
Relative density:	Not determined.
· Vapor density:	Not determined.
	(Cont'd. on page 7

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

		(Cont'd. of page
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol	water): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Other information	No relevant information available.	

10 Stability and reactivity

· Reactivity: No relevant information available.

- · Chemical stability:
- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- [•] Possibility of hazardous reactions
- Highly flammable liquid and vapor.

Reacts violently with oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Toxic fumes may be released if heated above the decomposition point.

Conditions to avoid

Keep away from heat and direct sunlight. Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

Incompatible materials Oxidizing agents

Hazardous decomposition products

Under fire conditions only: Carbon monoxide and carbon dioxide

11 Toxicological information

[·] Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 >5000 mg/kg (rat)

142-82-5 heptane

Oral LD50 >5000 mg/kg (rat)

Primary irritant effect:

· On the skin: Irritant to skin and mucous membranes.

• On the eye: Based on available data, the classification criteria are not met.

(Cont'd. on page 8)

Safety Data Sheet

Acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 7)

• Sensitization: Contains natural rubber latex. May produce an allergic reaction.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

· Carcinogenicity: Based on available data, the classification criteria are not met.

• Reproductive toxicity: Based on available data, the classification criteria are not met.

· STOT-single exposure: May cause drowsiness or dizziness.

· STOT-repeated exposure: Based on available data, the classification criteria are not met.

· Aspiration hazard: May be fatal if swallowed and enters airways.

12 Ecological information

· Toxicity

· Aquatic toxicity Toxic for aquatic organisms

· Persistence and degradability No relevant information available.

- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.

[•] Additional ecological information

· General notes:

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

· Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous. (Cont'd. on page 9)

Printing date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 8)

• Uncleaned packagings
 • Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1133
UN proper shipping name DOT, ADR, IMDG, IATA	ADHESIVES
Transport hazard class(es)	
DOT	
NAMMA LOT	
Class	3 Flammable liquids
Label	3
ADR	
Class	3 (F1) Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards	Product contains environmentally hazardo
	substances: heptane
Marine pollutant:	
Yes	
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33

Printing Date: June 28, 2024

Revision Date: June 28, 2024

	(Cont'd. of pa
EMS Number:	F-E,S-D
Transport in bulk according MARPOL73/78 and the IBC (
Transport/Additional inform	nation:
DOT	
Limited Quantity for pack	kages less than 30 kg gross and inner packagings less than 1 L each.
Labeling as a Marine Pollutant consists of a maximum capacity greater than 400 kg (882 pounds	t is only required for bulk single package shipments. Bulk package of greater than 450 L (119 gallons) for a liquid and a maximum net mass) for a solid. (See 171.4(c))
ADR	
Limited Quantity for pack	kages less than 30 kg gross and inner packagings less than 1 L each.
inner packaging of 5 L or less for	single or combination packagings containing a net quantity per single r liquids or having a net mass per single or inner packaging of 5 kg or isions relevant to marine pollutants. (See 5.2.8.1)
IMDG	
	kages less than 30 kg gross and inner packagings less than 1 L each.
Marine pollutants packaged in s inner packaging of 5 L or less for	single or combination packagings containing a net quantity per single r liquids or having a net mass per single or inner packaging of 5 kg or isions relevant to marine pollutants. (See 2.10.2.7)
Marine pollutants packaged in s inner packaging of 5 L or less for	r liquids or having a net mass per single or inner packaging of 5 kg or

(Cont'd. on page 11)

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 10)

15 Regulatory information	
 Safety, health and environmental regulations/legislation specific for the substance mixture United States (USA) SARA 	ce or
· Section 302 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act)	
All ingredients are listed.	
· Proposition 65 (California)	
· Chemicals known to cause cancer:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency):	
142-82-5 heptane	D
· IARC (International Agency for Research on Cancer):	
None of the ingredients are listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health):	
None of the ingredients are listed.	
· Canadian Domestic Substances List (DSL):	
All ingredients are listed.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision June 28, 2024 / June 28, 2024

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods

(Cont'd. on page 12)

Printing Date: June 28, 2024

Revision Date: June 28, 2024

Trade name: Bead Sealer

(Cont'd. of page 11) DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxique vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com