Page: 1/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

1 Identification

· Product identifier

· Trade name: Black Tire Paint · Product code: 14-154,14-156

· Recommended use and restriction on use

· Recommended use: Paint

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

31 Incorporated 100 Enterprise Dr.

Newcomerstown, OH 43832 Phone: (740) 498-8324

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS05

· Signal word: Danger

· Hazard statements:

H314 Causes severe skin burns and eye damage.

· Precautionary statements:

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor. P363 Wash contaminated clothing before reuse.

(Cont'd. on page 2)

Page: 2/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:				
1336-21-6	ammonia, aqueous solution	♦ Skin Corr. 1B, H314; Eye Dam. 1, H318	10-35%	
1333-86-4	carbon black		<1%	
25322-68-3	polyethylene glycol		<1%	

· Additional information: For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately rinse with water.

Seek immediate medical help for blistering or open wounds.

· After eye contact:

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Headache

Breathing difficulty

Coughing, dizziness, if inhaled.

Strong caustic effect on skin and mucous membranes.

Strong irritant with the danger of severe eye injury.

May cause respiratory irritation.

· Danger:

Danger of impaired breathing.

Vapours may cause drowsiness and dizziness.

Causes severe skin burns and eye damage.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 2)

Danger of gastric perforation.

Indication of any immediate medical attention and special treatment needed:

If necessary oxygen respiration treatment.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information: No relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only outdoors or in a well-ventilated area.

Keep away from heat and direct sunlight.

· Information about protection against explosions and fires:

Keep respiratory protective device available.

(Cont'd. on page 4)

Page: 4/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 3)

- Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Further information about storage conditions:

Keep containers tightly sealed.

Protect from heat and direct sunlight.

Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

oontroi paran	control parameters				
· Components w	· Components with limit values that require monitoring at the workplace:				
1333-86-4 carbon black					
PEL (USA)	Long-term value: 3.5 mg/m³				
REL (USA)	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C				
TLV (USA)	Long-term value: 3* mg/m³ *inhalable fraction				
EL (Canada)	Long-term value: 3 mg/m³ IARC 2B				
EV (Canada)	Long-term value: 3.5 mg/m³				
LMPE (Mexico)	Long-term value: 3* mg/m³ A3, *fracción inhalable				
25322-68-3 poly	yethylene glycol				
WEEL (USA)	Long-term value: 10 mg/m³ (H); MW>200				

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Engineering controls: Use only outdoors or in a well-ventilated area.
- · Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For large spills, respiratory protection may be advisable.

(Cont'd. on page 5)

Page: 5/11

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

· Protection of hands:

(Cont'd. of page 4)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment No relevant information available.
- · Risk management measures No relevant information available.

Physical and chemical properties				
Information on basic physical a	and chemical properties			
· Appearance:				
Form:	Viscous liquid.			
Color:	Black			
Odor:	Not determined.			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
Melting point/Melting range:	Not determined.			
· Boiling point/Boiling range:	Not determined.			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not applicable.			
· Auto-ignition temperature:	Not determined.			
Decomposition temperature:	Not determined.			
Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapor pressure:	Not determined.			
· Density:	Not determined.			
· Relative density:	Not determined.			
· Vapor density:	Not determined.			
· Evaporation rate:	Not determined.			
		(Cont'd. on pag		

Page: 6/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 5)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

To avoid thermal decomposition, do not overheat.

· Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

· Conditions to avoid

Store away from oxidizing agents.

Keep away from heat and direct sunlight.

- · Incompatible materials Oxidizing agents
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1333-86-4 carbon black

Oral LD50 10000 mg/kg (rat)

- · Primary irritant effect:
- On the skin: Caustic effect on skin and mucous membranes.
- · On the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.

IARC (International Agency for Research on Cancer):

1333-86-4 carbon black

2B

NTP (National Toxicology Program):

None of the ingredients are listed.

(Cont'd. on page 7)

Page: 7/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion. Inhalation.

Eye contact.

Skin contact.

- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · **STOT-single exposure:** May cause respiratory irritation.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity Toxic for aquatic organisms
- Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · **General notes:** Do not allow product to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

(Cont'd. on page 8)

Page: 8/11

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 7)

Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN2672
· UN proper shipping name · DOT, ADR, IMDG, IATA	AMMONIA SOLUTION
Transport hazard class(es)	
· DOT	
GORROSIVE	
· Class · Label	8 Corrosive substances 8
ADR	
· Class · Label	8 (C5) Corrosive substances 8
· IMDG, IATA	
· Class · Label	8 Corrosive substances 8
· Packing group · DOT, ADR, IMDG, IATA	III
Environmental hazards Marine pollutant: Yes	
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80 F A S B
· EMS Number: · Segregation groups	F-A,S-B Alkalis
Transport in bulk according to Ani MARPOL73/78 and the IBC Code	
WAINFULTSITO AIIU LIIE IDU COUE	Not applicable. (Cont'd. on pa

Page: 9/11

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

acc. to OSHA HOS (290FK 1910.1200) and While 2015 regulations

Trade name: Black Tire Paint

Printing Date: July 01, 2024

(Cont'd. of page 8)

Revision Date: July 01, 2024

· Transport/Additional information:

· DOT



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· ADR



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.8.1)

· IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

·IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Cont'd. on page 10)

Page: 10/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing Date: July 01, 2024 Revision Date: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 9)

· Section 313 (Specific toxic chemical listings):

1336-21-6 ammonia, aqueous solution

TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 carbon black

2B

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision July 01, 2024 / July 01, 2024
- · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxique vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

(Cont'd. on page 11)

Page: 11/11

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 01, 2024 Revision: July 01, 2024

Trade name: Black Tire Paint

(Cont'd. of page 10)

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com