

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

1 Identification

- **Product identifier**
- **Trade name:** **Rubber Compound**
- **Article number:** 14-438A, 14-438B
- **Recommended use and restriction on use**
- **Recommended use:** Tire maintenance.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
- Flam. Liq. 2 H225 Highly flammable liquid and vapor.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2B H320 Causes eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Carc. 2 H351 Suspected of causing cancer.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H225 Highly flammable liquid and vapor.
H315+H320 Causes skin and eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 1)

- H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
 H304 May be fatal if swallowed and enters airways.






Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe mist/vapors/spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P331 Do NOT induce vomiting.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a poison center/doctor if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Components:

108-88-3	Toluene  Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
9006-04-6	natural rubber latex  Skin Sens. 1B, H317	25-50%
1333-86-4	Carbon black  Carc. 2, H351	10-25%

Additional information: For the wording of the listed Hazard Statements, refer to section 16.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Headache

Breathing difficulty

Coughing, dizziness, if inhaled.

Irritant to skin and mucous membranes.

Allergic reactions

Causes eye irritation.

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

Disorientation

· Danger:

May be fatal if swallowed and enters airways.

Danger of impaired breathing.

Vapours may cause drowsiness and dizziness.

Danger of pulmonary edema.

Danger of pneumonia.

Danger of disturbed cardiac rhythm.

Danger of convulsion.

Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.

Suspected of causing cancer.

· Indication of any immediate medical attention and special treatment needed:

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation, possible shock treatment.

Later observation for pneumonia and pulmonary edema.

If necessary oxygen respiration treatment.

If swallowed or in case of vomiting, danger of entering the lungs.

Contains natural rubber latex. May produce an allergic reaction.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Highly flammable liquid and vapor.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:** Eliminate all ignition sources if safe to do so.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Protect from heat.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 4)

- Provide ventilation for receptacles.
- Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
 - Store away from foodstuffs.
 - Store away from oxidizers, strong acids, strong bases.
- **Further information about storage conditions:** Keep containers tightly sealed.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm
LMPE (Mexico)	Long-term value: 20 ppm A4, IBE

9006-04-6 natural rubber latex

TLV (USA)	Long-term value: 0.0001* mg/m ³ Skin; DSEN, RSEN;* inh. fraction
EL (Canada)	Long-term value: 0.001 mg/m ³ inhalable, Skin; S
EV (Canada)	Long-term value: 0.001 mg/m ³ as total proteins, inhalable, Skin
LMPE (Mexico)	Long-term value: 0.0001* mg/m ³ SEN, PIEL, *fracción inhalable

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 5)

· **Ingredients with biological limit values:**

108-88-3 Toluene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Exposure controls**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.
Pregnant women should strictly avoid inhalation or skin contact.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Engineering controls:**

Provide adequate ventilation.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Ground/bond container and receiving equipment.

· **Breathing equipment:**

For spills, respiratory protection may be advisable.
Use suitable respiratory protective device when high concentrations are present.
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Solvent resistant protective clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 6)

· **Risk management measures** No relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· **Appearance:**

· **Form:** Liquid

· **Color:** Dark

· **Odor:** Solvent-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** 110 °C (230 °F)

· **Flash point:** 4 °C (39.2 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** 535 °C (995 °F)

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits**

· **Lower:** 1.2 Vol %

· **Upper:** 7.0 Vol %

· **Oxidizing properties:** Non-oxidizing.

· **Vapor pressure:** Not determined.

· **Density:** Not determined.

· **Relative density:** Not determined.

· **Vapor density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity**

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

· **Other information** No relevant information available.

10 Stability and reactivity

· **Reactivity:** No relevant information available.

· **Chemical stability:**

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 7)

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Reacts violently with oxidizing agents.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizing agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 Toluene

Oral	LD50	5,000 (rat)
Dermal	LD50	12,124 (rabbit)
Inhalative	LC50/4h	5,320 (mouse)

1333-86-4 Carbon black

Oral	LD50	10,000 (rat)
------	------	--------------

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** Contains natural rubber latex. May produce an allergic reaction.

- **IARC (International Agency for Research on Cancer):**

1333-86-4	Carbon black	2B
-----------	--------------	----

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:**

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 8)

May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1294
- **UN proper shipping name**
- **DOT, ADR, IMDG, IATA** TOLUENE
- **Transport hazard class(es)**
- **DOT**



(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 9)

· **Class** 3
· **Label** 3

· **ADR**



· **Class** 3 (F1)
· **Label** 3

· **IMDG, IATA**



· **Class** 3
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **IATA**

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 10)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 | Toluene

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 | Carbon black

· **Chemicals known to cause developmental toxicity for females:**

108-88-3 | Toluene

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 | Toluene

· **EPA (Environmental Protection Agency):**

108-88-3 | Toluene

II

· **IARC (International Agency for Research on Cancer):**

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 | Carbon black

2B

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any
(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing Date: July 01, 2024

Revision Date: July 01, 2024

Trade name: Rubber Compound

(Cont'd. of page 11)

specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com